

**In the Claims**

**Prior to calculating the fee,**

This listing of claims will replace the version presented in the International Application to which this U.S. application claims priority.

**Listing of Claims:**

- [c1] (currently amended): A method of removing particulate solids from an oil based drilling or completion fluid, wherein the fluid comprises a water-in-oil emulsion, the method comprising:  
exposing the fluid to an electric field having a strength lower than that required to coalesce the water droplets of the emulsion to electrically migrate particulate solids suspended therein, and  
collecting the migrated particulate solids to remove them from the fluid.
- [c2] (cancel)
- [c3] (currently amended): A method according to claim 1 ~~or 2~~, wherein the electric field has a strength less than 100,000 V/m.
- [c4] (currently amended): A method according to claim 3 ~~any one of the previous claims~~, wherein the strength of the electric field is controlled such that current and voltage remain proportional to each other.
- [c5] (currently amended): A method according to claim 4 ~~any one of the previous claims~~, wherein the fluid has a PV and a YP, and wherein the PV and/or the YP of the fluid are reduced as a result of the collection of the particulate solids.
- [c6] (currently amended): A method according to claim 1 ~~any one of the previous claims~~, wherein ~~the fluid contains~~ suspended particulate solids include clay particles.

- [c7] (currently amended): A method according to claim 1 ~~any one of the previous claims~~, wherein the ~~fluid contains~~ suspended particulate solids include weighting agent particles.
- [c8] (currently amended): A method according to claim 1 ~~any one of the previous claims~~, wherein the particulate solids in the fluid exposed to the electric field occupy at least 5 vol. % of the total fluid.
- [c9] (currently amended): A method according to claim 8 ~~any one of the previous claims~~, wherein the fluid exposed to the electric field is a shear-thinning fluid which forms a gel when quiescent.
- [c10] (currently amended): A method according to claim 1 ~~any one of the previous claims~~, further comprising:  
heating the fluid to enhance the collection of particulate solids.
- [c11] (currently amended): A method of recycling an oil based drilling or completion fluid by ~~performing the method of any one of the previous claims~~ comprising:  
exposing the fluid to an electric field to electrically migrate particulate solids suspended therein;  
collecting the migrated particulate solids to remove them from the fluid; and  
using a centrifuge or hydrocyclone to remove other particulate solids from the fluid.
- [c12] (cancel)
- [c13] (original): A method according to claim 1, including the step of using at least two electrodes to generate the electric field.
- [c14] (original): A method according to claim 1, including the step of using at least two electrodes to generate the electric field and a deposit removal system co-located with the electrodes.

- [c15] (original): A method according to claim 14, wherein deposit removal system is operated continuously or as a batch process.
- [c16] (cancel)
- [c17] (new): A method according to claim 1, wherein the fluid exposed to the electric field is a shear-thinning fluid which forms a gel when quiescent.
- [c18] (new): A method according to claim 11, further comprising:  
heating the fluid to enhance the collection of particulate solids.
- [c19] (new): A method according to claim 18, wherein the particulate solids in the fluid exposed to the electric field occupy at least 5 vol. % of the total fluid.
- [c20] (new): A method according to claim 19, wherein the fluid exposed to the electric field is a shear-thinning fluid which forms a gel when quiescent.
- [c21] (new): A method according to claim 19, wherein the strength of the electric field is less than 100,000 V/m.
- [c22] (new): A method according to claim 21, wherein the strength of the electric field is controlled such that current and voltage remain proportional to each other.
- [c23] (new): A method according to claim 22, wherein the fluid has a PV and a YP, the PV and/or the YP being reduced as a result of the collection of the particulate solids.